HLB SERIES-FT 2-0474

EAN 8422202204741



Reinforced nylon castors, especially indicated to support high-loads up to 1.250 Kg.

It is used in: logistics transport tools, outdoor area, internal logistics, mobile platforms, elevating platforms, transport cars, logistics for military missions material, heavy machinery in the construction sector, mobile cranes and sport centres.


Mainly used in the aeronautic sector, railway and automobilie factories. Clean rooms.

FT: especially indicated for food and chemical industry applications. Does not leave marks on floor. Reinforced. Canning factories.

Technical Data

Housing Type	**Fixed**
Fitting Type	**Plate**
Braking System	**Without Brake**
Material	**Nylon(Polyamide 6)**
Bearing	**Plain**
Diameter (mm)	**125**
Width of tyre (mm)	**42**
Plate dimensions (mm)	**150x110**
Distance between holes (mm)	**105x80**
Plate hole diameter (mm)	**10**
Overall height (mm)	**183**
Load	**600**
Unit Weight of the wheel (kg)	**2.636**
Volume (cm^3)	**3020**

CAD




To visualize the image with higher resolution and more technical details, please access to the CAD section

 Ruedas Alex, S.L.U. All rights reserved.

Brackets

Image not found or type unknown



Heavy fabricated castor made of welded steel up to 8 mm.Painted black.Combination of thrust ball bearing and tapered roller bearing in the swivel head: the upper for axial eff orts and the lower for radial efforts.Grease nipples on the swivel head and the wheel.Manufactured to European standards EN 12532/12533.

Similar products



2-0465



2-3377

Wheel



Reinforced nylon (Polyamid 6) wheel, white colour
Temperature range: -30º ÷ +80º

Rolling Resistence — Excelent

Noise during the march — Reasonable

Floor Protection — Reasonable

 Ruedas Alex, S.L.U. All rights reserved.